

Miniature Fuse, 5 x 20 mm, Time-Lag T, L, 250 VAC



IEC 60127-2 · 250 VAC · Time-Lag T

See below:

[Approvals and Compliances](#)

Description

- IEC Standard Fuse
- L = Low Breaking Capacity (Glass Tube)

Applications

- Primary Protection in Equipment

References

Pigtail Type [FST 5x20 Pigtail](#)
Assembled Fuseholder [OGN-SMD](#)
Fuse Kit [Fuse Kit FST 5x20](#); [Fuse Kit FST 5x20 / SP 5x20](#)

Weblinks

[pdf datasheet](#), [html-datasheet](#), [General Product Information](#), [Packaging details](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

[Application Note Primary Protection in Equipment](#) with further information on increased [Pulse Strength](#) and their test conditions according to international standards see [Impulse Withstand Voltage](#)

Technical Data

Rated Voltage	250 VAC
Rated current	0.05 - 20 A
Breaking Capacity	35 A - 200 A
Characteristic	Time-Lag T
Admissible Ambient Air Temp.	-55 °C to 125 °C
Climatic Category	55/125/21 acc. to IEC 60068-1
Material: Tube	Glass
Material: Endcaps	Nickel-Plated Copper Alloy
Unit Weight	1 g
Storage Conditions	0 °C to 60 °C, max. 70% r.h.
Product Marking	 , Rated current, Rated Voltage, Characteristic, Breaking Capacity, Approvals

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: FST 5x20

Approval Logo	Certificates	Certification Body	Description
	VDE Approvals	VDE	VDE Certificate Number: 40016601
	VDE Approvals	VDE	VDE Certificate Number:
	UL Approvals	UL	UL File Number: E41599
	CQC Approvals	CQC	CCC Certificate Number:
	CQC Approvals	CQC	CCC Certificate Number:
	METI Approvals	METI	Japan Electrical Safety and Environment technology Laboratories

Product standards

Product standards that are referenced

Organization	Design	Standard	Description
	Designed according to	UL 248-14	Low voltage fuses - Part 14: Additional fuses
	Designed according to	CSA22.2 No. 248.14	Low-Voltage Fuses - Part 14: Supplemental Fuses

Application standards

Application standards where the product can be used


Organization	Design	Standard	Description
	Designed for applications acc.	IEC/UL 60950	IEC 60950-1 includes the basic requirements for the safety of information technology equipment.

Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
	RoHS	SCHURTER AG	EU Directive RoHS 2011/65/EU
	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.


Dimension [mm]



Pre-Arcing Time

Rated Current In	1.5 x In min.	2.1 x In max.	2.75 x In min.	2.75 x In max.	4.0 x In min.	4.0 x In max.	10.0 x In min.	10.0 x In max.
0.05 A - 0.1 A	60 min	120 s	200 ms	10 s	40 ms	3 s	10 ms	300 ms
0.125 A - 6.3 A	60 min	120 s	600 ms	10 s	150 ms	3 s	20 ms	300 ms
8 A - 20 A	30 min	120 s	600 ms	10 s	150 ms	3 s	20 ms	300 ms

Time-Current-Curves



All Variants

Rated Current [A]	Rated Voltage [VAC]	Breaking Capacity	Voltage Drop 1.0 I _n max. [mV]	Voltage Drop 1.0 I _n typ. [mV]	Power Dissipation 1.5 I _n max. [mW]	Power Dissipation 1.5 I _n typ. [mW]	Melting I _t 10.0 I _n typ. [A ² s]						Order Number
0.05	250	1)	3500	950	1600	125	0.0363	•	•	•	•	•	0034.3104
0.063	250	1)	3000	1300	1600	200	0.0401	•	•	•	•	•	0034.3105
0.08	250	1)	3000	1100	1600	300	0.057	•	•	•	•	•	0034.3106
0.1	250	1)	2500	565	1600	155	0.107	•	•	•	•	•	0034.3107
0.125	250	1)	2000	400	1600	200	0.064	•	•	•	•	•	0034.3108
0.16	250	1)	1900	415	1600	185	0.23	•	•	•	•	•	0034.3109
0.2	250	1)	1500	270	1600	200	0.256	•	•	•	•	•	0034.3110
0.25	250	1)	1300	210	1600	200	0.238	•	•	•	•	•	0034.3111
0.315	250	1)	1100	170	1600	200	0.544	•	•	•	•	•	0034.3112
0.4	250	1)	1000	150	1600	200	0.768	•	•	•	•	•	0034.3113
0.5	250	1)	900	160	1600	200	3	•	•	•	•	•	0034.3114
0.63	250	1)	300	160	1600	300	4.35	•	•	•	•	•	0034.3115
0.8	250	1)	250	120	1600	300	3.85	•	•	•	•	•	0034.3116
1	250	1)	150	60	1600	200	3.3	•	•	•	•	•	0034.3117
1.25	250	1)	150	60	1600	300	5.5	•	•	•	•	•	0034.3118
1.6	250	1)	150	60	1600	300	10.5	•	•	•	•	•	0034.3119
2	250	1)	150	60	1600	300	16	•	•	•	•	•	0034.3120
2.5	250	1)	120	60	1600	400	21.9	•	•	•	•	•	0034.3121
3.15	250	1)	100	60	1600	500	47	•	•	•	•	•	0034.3122
4	250	2)	100	60	1600	800	68.3	•	•	•	•	•	0034.3123
5	250	2)	100	60	1600	900	102	•	•	•	•	•	0034.3124
6.3	250	2)	100	60	1600	1000	190	•	•	•	•	•	0034.3125
8	250	2)	100	60	4000	1300	275	•	•	•	•	•	0034.3126
10	250	2)	100	60	4000	1300	520	•	•	•	•	•	0034.3127
12.5	250	2)	-	60	-	2500	750	•	•	•	•	•	0034.3128
16	250	2)	-	60	-	3300	1638	•	•	•	•	•	0034.3129
20	250	2)	-	60	-	4200	3057	•	•	•	•	•	0034.3130

Most Popular.

Rated Cur- rent [A]	Rated Vol- tage [VAC]	Breaking Capacity	Voltage Drop 1.0 I _n max. [mV]	Voltage Drop 1.0 I _n typ. [mV]	Power Dissi- pation 1.5 I _n max. [mW]	Power Dissi- pation 1.5 I _n typ. [mW]	Melting I ² t 10.0 Intyp. [A²s]	     	Order Number
------------------------	--------------------------	----------------------	---	---	--	--	--	--	--------------

Availability for all products can be searched real-time:<https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

- 1) 35 A @ 250 VAC
- 2) 10 x I_n @ 250 VAC

Packaging Unit	xxxx.xxxx xxxx.xxxx.G	Small Box Pack (10 pcs.) Bulk 128 x 91 x 60 mm (1000 pcs.)
----------------	--------------------------	---