

---

Item no.: 770-503  
Product description: RELIEF HOUSING 3 POLE WIRE DIAMETER 8-12 MM

---



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

|                    |             |
|--------------------|-------------|
| Product group      | 20 (WINSTA) |
| pole count         | 3           |
| Weight             | 9.433 g     |
| Color              | black       |
| Height             | 15 mm       |
| Height             | 0.591 in    |
| Width              | 34.6 mm     |
| Width              | 1.362 in    |
| Depth              | 50 mm       |
| Depth              | 1.97 in     |
| Customs Tariff No. | 85389099    |
| Country of Origin  | Deutschland |



| Item no. | Admission office | Approval no.       | Voltage [V] | Current [A] | Cross section [ mm² ] |
|----------|------------------|--------------------|-------------|-------------|-----------------------|
| 770-503  | ABS              | 06-HG154986/11-PDA |             |             |                       |
| 770-503  | CCA              |                    |             |             |                       |
| 770-503  | cURus            | E45171             |             |             |                       |
| 770-503  | DNV              | E-9217             |             |             |                       |
| 770-503  | GL               | 42875-02HH         |             |             |                       |
| 770-503  | KEMA             |                    |             |             |                       |
| 770-503  | LR               | 02/20050(E3)       | 250         | 25          | 2,5                   |
| 770-503  | PRS              | TE/1719/880590/08  |             |             |                       |
| 770-503  | PSE              | JET0695-43009-1001 |             |             |                       |
| 770-503  | VDE              | Ausweis.Nr.30726   | 250/400     | 16/25       | 0,5-4,0               |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected