

ERSADUR long-life soldering tip series 832, 842 and 852



- ANALOG 60/60 A
- ANALOG 80/80 A
- DIGITAL 80 A
- DIGITAL 2000 A with POWER TOOL soldering iron
- ELS 8000/M/D

- ERSA 15+ / 25+ / 35+
- MICRO-CON 60 iA with POWER TOOL soldering iron
- MS 6000 / MS 8000/D
- MULTI-PRO
- MULTI-SPRINT

- MULTI-TC
- RDS 80
- TWIN 80 A with ERGO TOOL

0832UD/UDLF pencil point, 0.4 mm Ø, extended	0832SD/SDLF pencil point, 0.8 mm Ø, extended	0832BD/BDLF pencil point, 1.0 mm Ø	0832YD/YDLF chisel-shaped, 1.6 mm
0832CD/CDLF chisel-shaped, 2.2 mm	0832KD/KDLF chisel-shaped, 2.2 mm, extended	0832ED/EDLF chisel-shaped, 3.2 mm	0832VD/VDLF chisel-shaped, 5.0 mm
0832FDLF angled face, 2.0 mm	0832TDLF angled face, 3.0 mm Ø	0832NDLF angled face, 4.0 mm Ø	0832PW PowerWell with concave portion
0832HD SolderWell with concave portion, bent	0832AD PLCC blade, 1.5 mm	0852OD PLCC blade, 2.0 mm	0832WD chisel-shaped, 2.5 mm, bent
0832RD chisel-shaped, 5.0 mm, bent	0832GDLF angled face, 14 mm, 35°	0832LDLF angled face, 17 mm, 35°	0832MDLF angled face on both sides, 8 mm
0842UD/UDLF pencil point, 0.4 mm Ø, extended	0842SD/SDLF pencil point, 0.8 mm Ø, extended	0842BD/BDLF pencil point, 1.0 mm Ø	0842YD/YDLF chisel-shaped, 1.6 mm
0842CD/CDLF chisel-shaped, 2.2 mm	0842KD/KDLF chisel-shaped, 2.2 mm, extended	0842ED/EDLF chisel-shaped, 3.2 mm	0842ID pencil point, 0.4 mm Ø, bent
0842JD chisel-shaped, 2.2 mm, bent	0852GD angled face, 8.0 mm	0852VD chisel-shaped, 5.0 mm	

Dimensions without pre-tinning