

MORSETTIERE PER C.S.
TERMINAL BLOCKS FOR P.C.B.
BARRETTES DE CONNEXION POUR C.I.
ANSCHLUßKLEMMEN FÜR LEITERPLATTE



TIPO
TYPE
TYPE
TYP




PASSO
PITCH
PAS
RASTERMAß



CII 5/...



CII 5/...SQ



P	L mm
5	5 x p
5,08	5,08 x p
10	10 x p-5
10,16	10,16 x p-5,08

MODULI COMPONENTI
A CARRELLO
2/3 POLI

RISING CLAMP
INTERLOCKING MODULES
2/3 POLES

BORNE ETREIZ MOBILE
ELEMENTS MODULAIRES
2/3 POLES

BEWEGLICHER
KLEMMKÖRPER
2/3 POLIG ANREIHBAR



Corpo isolante Verde	Insulating body Green	Corps isolant Vert	Isolierkörper Grün	PA68 UL94VO
Vite	Screw	Vis	Schraube	M3-C8R+Zn
Morsetto	Clamp	Borne	Klemmkörper	CuZn40 Pb2+Ni
Contatto	Pin	Contacte	Kontakt	CuZn37+Ni+Sn
Coppia di torsione	Testing torque	Couple de serrage	Zul. Drehmoment	0,5 Nm
Sezione	Section	Section	Querschnitt	1,5 mm ²
Vite imperdibile	Captive screw	Vis imperdable	Schraube unvelierbar	-
Foro di montaggio	P.C.B. mounting hole	Perçage C. I.	Leiterplattenbohrung	Ø 1,3 mm
Corrente nominale	Nominal current	Courant nominal	Strombelastbarkeit	17,5 A
Tensione	Voltage	Tension	Betriebsspannung	250/750 V
Temperatura	Temperature	Température	Temperatur	85°C
Grado di protezione	Protection index	Degré de protection	Schutzklasse	IP00
Resistenza di isolamento	Insulation resistance	Résistance d'isolement	Isolationswiderstand	≥ 5 MΩ
Rigidità dielettrica	Dielectric strength	Rigidité diélectrique	Durchschlagsfestigkeit	≥ 2500 Vac/60"