


SPECIFICATION FOR APPROVAL

COMMODITY	PK CHOKE		SPEC NO.	SP-0140912001
ITEM	COIL1016-0.68	Green	A	TRR-002

(1) DIMENSION: (UNIT: mm)			DIM.	TOL.
		A	11.5	MAX.
		B	17.5	MAX.
		C	16.0	±3.0
		D	0.8	±0.1
		E	6.0	±0.5
		F	3.0	MAX.
		G		
		H		
		I		
		J		

(2) ELECTRICAL CHARACTERISTIC			TEST INSTRUMENTS.
INDUCTANCE	680 ± 10%	μH	☒ AGILENT 4294A Precision Impedance Analyzer. ☐ AGILENT 4285A Precision L.C.R. Meter. ☐ HP-4286A RF L.C.R. Meter. ☒ ZENTECH 3302 Automatic Components Analyzer. ☐ ZENTECH 101 L.C.R. Meter. ☐ WAYNE KERR 6420 Precision Impedance Analyzer. ☒ ZENTECH 1320 BIAS CURRENT. ☒ ZENTECH 502AC Resistance Meter. ☐ ADEX AX-1155B DC Low Ohm Meter.
TEST FREQUENCY	1	kHz	
TEST VOLT	0.25	V	
RDC	888 (max)	mΩ	
Isat	1.20 (max)	A	
Irms	1.2 (max)	A	

REMARK :

- Inductance drop = 10% typ at Isat.
- ΔT = 40°C rise typ at Irms.

SPECIFICATION FOR APPROVAL

COMMODITY		PK CHOKE		SPEC NO.	SP-0140912001
ITEM		COIL1016-0.68	Green	A	TRR-002
(3) Material List					
NO	ITEM	MATERIAL	NOTE		
1	CORE	C5N DRWW 10*16(SW) (B6 F10.5 P6)			
2	WIRE	2UEW 130°C CLASS 0.32/132Ts			
3	SOLDER	Sn 99.3 % / Cu 0.7%			
4	TUBE	UL 10*18			