


# SPECIFICATION FOR APPROVAL

|           |              |       |          |               |
|-----------|--------------|-------|----------|---------------|
| COMMODITY | PK CHOKE     |       | SPEC NO. | SP-0111202104 |
| ITEM      | COIL1016-5.6 | Green | D        | QRRD-01-02    |

| (1) DIMENSION: (UNIT: mm)                                                         |  |   | DIM. | TOL. |
|-----------------------------------------------------------------------------------|--|---|------|------|
|  |  | A | 11.5 | MAX. |
|                                                                                   |  | B | 17.5 | MAX. |
|                                                                                   |  | C | 16.0 | ±3.0 |
|                                                                                   |  | D | 0.8  | ±0.1 |
|                                                                                   |  | E | 6.0  | ±0.5 |
|                                                                                   |  | F | 3.0  | MAX. |
|                                                                                   |  | G |      |      |
|                                                                                   |  | H |      |      |
|                                                                                   |  | I |      |      |
|                                                                                   |  | J |      |      |

| (2) ELECTRICAL CHARACTERISTIC |            |     | TEST INSTRUMENTS.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------------------|------------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| INDUCTANCE                    | 5.6 ± 10%  | mH  | <input checked="" type="checkbox"/> AGILENT 4294A Precision Impedance Analyzer.<br><input type="checkbox"/> AGILENT 4285A Precision L.C.R. Meter.<br><input type="checkbox"/> HP-4286A RF L.C.R. Meter.<br><input checked="" type="checkbox"/> ZENTECH 3302 Automatic Components Analyzer.<br><input type="checkbox"/> ZENTECH 101 L.C.R. Meter.<br><input type="checkbox"/> WAYNE KERR 6420 Precision Impedance Analyzer.<br><input checked="" type="checkbox"/> ZENTECH 1320 BIAS CURRENT.<br><input checked="" type="checkbox"/> ZENTECH 502AC Resistance Meter.<br><input type="checkbox"/> ADEX AX-1155B DC Low Ohm Meter. |
| TEST FREQUENCY                | 1          | kHz |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| TEST VOLT                     | 0.25       | V   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| RDC                           | 4.81 (max) | Ω   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Isat                          | 0.28 (max) | A   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Irms                          | 0.50 (max) | A   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                               |            |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## REMARK :

1. Inductance drop = 10% typ at Isat.
2. ΔT = 40°C rise typ at Irms.

## SPECIFICATION FOR APPROVAL

|                   |        |                                  |             |          |               |
|-------------------|--------|----------------------------------|-------------|----------|---------------|
| COMMODITY         |        | PK CHOKE                         |             | SPEC NO. | SP-0111202104 |
| ITEM              |        | COIL1016-5.6                     | Green       | D        | QRRD-01-02    |
| (3) Material List |        |                                  |             |          |               |
| NO                | ITEM   | MATERIAL                         | NOTE        |          |               |
| 1                 | CORE   | DR2W 10*16 Or other's equivalent |             |          |               |
| 2                 | WIRE   | UEW Or other's equivalent        | 130°C CLASS |          |               |
| 3                 | SOLDER | 100H Or other's equivalent       |             |          |               |
| 4                 | TUBE   | Heat Shrinkable tube             |             |          |               |
|                   |        |                                  |             |          |               |
|                   |        |                                  |             |          |               |
|                   |        |                                  |             |          |               |
|                   |        |                                  |             |          |               |
|                   |        |                                  |             |          |               |