




FEATURES

- ※ Compact size 3.5x6 mm
- ※ Sharp click feeling
- ※ Choice of SMT terminal type


APPLICATION

- ※ Audio, OA equipment
- ※ Instrumentation
- ※ Industrial

SPECIFICATION

Contact Rating	50mA, 12V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	250V AC/1 minute
Operating Force	125±50gf, Black(K) 160±50gf, Brown(N) 260±50gf, Red(R) 320±80gf, Salmon(S) 520±130gf, Yellow(Y)
Travel	0.25mm
Operating Life	30,000 cycles for 520/320/260gf 50,000 cycles for 160/125gf
Operating Temp.	-25°C ~ +70°C
Storage Temp.	-30°C ~ +80°C

CIRCUIT



PACKAGE

<Tube>

135 pcs

<Bulk>

1000 pcs

<Tape & Reel>

DTSM(L)-31: 1800 pcs

DTSM(L)-32: 1600 pcs

HOW TO ORDER

D T S - 3

□:Through Hole
M:S.M.T./J-bend outward
ML:S.M.T./Flat
MF:S.M.T./Gull-wing


Package:
□=Bag(Through Hole Only)
B=Tube Package
T/R=Tape & Reel

V=RoHS & Lead Free Solderable
Q=Halogen Free


Dimension H:
1=4.3mm
2=5.0mm

Operating Force:
K=Black, 125gf
N=Brown, 160gf
R=Red, 260gf
S=Salmon, 320gf
Y=Yellow, 520gf >Not Available For Halogen Free

DTS-3




PART NO.	H
DTS-31	4.30
DTS-32	5.00




P.C.B. LAYOUT

DTSM-3




PART NO.	H
DTSM-31	4.30
DTSM-32	5.00




P.C.B. LAYOUT

DTSML-3




PART NO.	H
DTSML-31	4.30
DTSML-32	5.00




P.C.B. LAYOUT

DTSMF-3



PART NO.	H
DTSMF-31	4.30
DTSMF-32	5.00



P.C.B. LAYOUT