


NYLON-INSULATED CORD END TERMINALS (E SERIES)

MAXIMUM ELECTRIC CURRENT:

A.W.G.	26	24	22	20	18
AMP.	5.5	7	9	12	17

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.
CONNECTOR MATERIAL: COPPER TUBE.
INSULATION MATERIAL: NYLON


WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION inch mm						FRENCH COLOR	GERMAN COLOR	DIN COLOR	CRIMPING TOOL				
		F	L	W	B	D	C								
24 A.W.G. 0.25 mm ²	E0205 ☉	.197 5.0	.370 9.4					VIOLET 	LIGHT BLUE 		K.S. MODEL LY8-060 WITH DIE INDEX NO:0.25-0.75				
	E0206	.236 6.0	.409 10.4												
	E0208	.315 8.0	.488 12.4												
22 A.W.G. 0.34 mm ²	E0305 ☉	.197 5.0	.370 9.4					PINK 	TURQUOISE 						
	E0306	.236 6.0	.409 10.4												
	E0308	.315 8.0	.488 12.4												
	E0309	.354 9.0	.528 13.4												
20 A.W.G. 0.5 mm ²	E0505 ☉	.197 5.0	.433 11.0					WHITE 	ORANGE 	WHITE 	K.S. MODEL KST2000L WITH DIE INDEX NO:0.5 OR K.S. MODEL LY8-060 WITH DIE INDEX NO:0.25-0.75				
	E0506	.236 6.0	.472 12.0												
	E0508	.315 8.0	.551 14.0												
	E0509	.354 9.0	.591 15.0												
	E0510	.394 10.0	.630 16.0												
	E0512	.472 12.0	.709 18.0												
18 A.W.G. 0.75 mm ²	E7505 ☉	.197 5.0	.445 11.3					BLUE 	WHITE 	GREY 	K.S. MODEL KST2000L WITH DIE INDEX NO:0.75 OR K.S. MODEL LY8-060 WITH DIE INDEX NO:0.25-0.75				
	E7506	.236 6.0	.484 12.3												
	E7508	.315 8.0	.563 14.3												
	E7508-L	.315 8.0	.571 14.5												
	E7510	.394 10.0	.642 16.3												
	E7510-L	.394 10.0	.650 16.5												
	E7512	.472 12.0	.720 18.3												
	E7512-L	.472 12.0	.728 18.5												
	E7518	.709 18.0	.957 24.3												
	E7518-L	.709 18.0	.965 24.5												
18 A.W.G. 1.0 mm ²	E1006	.236 6.0	.472 12.0	.118 3.0				RED 	YELLOW 	RED 	K.S. MODEL KST2000L WITH DIE INDEX NO:1 OR K.S. MODEL LY8-060 WITH DIE INDEX NO:1-1.5				
	E1006-L	.236 6.0	.492 12.5	.650 3.3											
	E1008	.315 8.0	.551 14.0	.118 3.0											
	E1008-L	.315 8.0	.571 14.5	.130 3.3											
	E1010	.394 10.0	.630 16.0	.118 3.0											
	E1010-L	.394 10.0	.650 16.5	.650 3.3											
	E1012	.472 12.0	.709 18.0	.118 3.0											