



E2E-X4B1T12 5M

Proximity sensor, inductive, nickel-brass, short body, M12, shielded, 4 mm, DC, 3-wire, PNP NO, IO-Link COM3, 5 m cable

Technické údaje

Size	M12
Mounting type	Quasi-flush
Sensing distance	4 mm
Overall length of sensor	47.1 mm
Thread length	29 mm
Material housing	Brass, nickel plated
Output type	IO-Link, PNP
Operation mode	NO
Connection method	Cable
Cable specifications	PVC (oil-resistant)
Cable length	5 m
IO-Link function	✓
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP67G/IP69K

Příslušenství



Y92E-J12S18

Mounting Sleeves e-jig for M12 Prox

CAD knihovny



E2E NEXT

Katalogový list

EN PDF 40,0 MB



E2E(Q) - Basic Models

Rejstříkový seznam

EN PDF 719,1 KB



E2E(Q) - Premium Models

Rejstříkový seznam

EN PDF 719,1 KB



E2E[Q]-XxBxxxx

Soubor IO-Link IODD

EN ZIP 1,3 MB



EAC Mark removal

Upozornění na ukončení výroby

EN PDF 220,8 KB



IO-Link Series

Brožura

EN PDF 6,4 MB