

REV	DESCRIPTION	DATE
△	RDK-96131	張馨尹 2008/01/04
△	RDCM-102040	張馨尹 2013/10/23
△	RDCM-102188	謝婉如 2013/11/11

NOTE :

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	12	10	
AMP.	20	24	
2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
3. INSULATION MATERIAL : VINYL
4. INSULATION COLOR : YELLOW
5. TERMINAL MATERIAL : BRASS
6. WIRE RANGE : 12-10 A.W.G. (4 - 6 mm²)
7. NEMA TAB : 0.047 inch * 0.370 inch (1.2 mm * 9.40 mm)
8. DOUBLE CRIMP : WITH COPPER SLEEVE ON BARREL
9. TERMINAL SURFACE TREATMENT : TIN PLATED
10. TERMINAL THICKNESS : 0.50 mm

Tolerance Unless Otherwise Specified		
0 > 6 mm ± 0.20	ANGLE	
6 > 18 mm ± 0.30	0°	° REF ±
18 > 30 mm ± 0.40	°	° ±
30 > 75 mm ± 0.50	°	° ±

NAME	VINYL-INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS				UNIT	mm	
PART NO.	FDD5-375	MATERIAL	-----	APPROVE			
NUMBER	KA-951324-C	SCALE	SHEET	PAGE	CHECKED		
DATE	2006/09/11	4/1	1-3	10/2	DRAWN	謝婉如	

KST. K.S. TERMINALS INC.

