

QUICK SPLICE CONNECTORS






MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18	16	14	12	10
AMP.	3	4	7	10	15	20	24

MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.

INSULATION MATERIAL : P.P.

TERMINAL MATERIAL : BRASS

A.W.G.	ITEM NO.	W mm(inch)	L mm(inch)	COLOR	FIGURE
22-18	878100	20.0 (.787)	27.0 (1.063)	RED	 
18-14	878101	20.0 (.787)	27.0 (1.063)	BLUE	 
18-14	878101-WHITE	20.0 (.787)	19.3 (.760)	WHITE	 
12-10	878201	20.5 (.807)	34.5 (1.358)	YELLOW	 



MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14	12	10
AMP.	3	4	7	10	15	20	24

MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.

INSULATION MATERIAL : NYLON

TERMINAL MATERIAL : BRASS

A.W.G.	ITEM NO.	W mm(inch)	L mm(inch)	COLOR	FIGURE
22-16	878010D	9.8 (.386)	37.0 (1.457)	RED	 
12-10 18-14	878211D	9.8 (.386)	37.0 (1.457)	BROWN	 

QUICK SPLICE CONNECTORS




MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14	12
AMP.	3	4	7	10	15	20

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL: NYLON

TERMINAL MATERIAL: BRASS

A.W.G.	ITEM NO.	Suggested Mate With Male Tab	W mm(inch)	L mm(inch)	FIGURE
22-18	878006	MDFNY1-250	9.8 (.386)	37.0 (1.457)	 
18-14	878106	MDFNY2-250	9.8 (.386)	37.0 (1.457)	 
12	878206	MDFNY5-250	9.8 (.386)	37.0 (1.457)	 

  ALL LISTED

BUTT SPLICE & OTHER CONNECTORS

C7




MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14	12
AMP.	3	4	7	10	15	20

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL: NYLON

TERMINAL MATERIAL: BRASS

A.W.G.	ITEM NO.	Suggested Mate With Male Tab	W mm(inch)	L mm(inch)	FIGURE
22-18	878006D	MDFNY1-250	9.3 (.366)	40.2 (1.583)	DOUBLE CRIMP  
18-14	878106D	MDFNY2-250	9.3 (.366)	40.2 (1.583)	DOUBLE CRIMP  
12	878206D	MDFNY5-250	9.3 (.366)	40.2 (1.583)	DOUBLE CRIMP  

FEMALE DISCONNECTS-FUSE HOLDER

MAXIMUM ELECTRIC CURRENT:


A.W.G.	18	16	14
AMP.	7	10	15

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL:

878104, 878107, 878109 : P.P.

TERMINAL MATERIAL: BRASS

A.W.G.	ITEM NO.	Suggested Mate With Blade Fuse	W mm(inch)	L mm(inch)	FIGURE
18-14	972	FATC SERIES	35.0 (1.378)	34.0 (1.339)	 

QUICK SPLICE CONNECTORS

MAXIMUM ELECTRIC CURRENT:





A.W.G.	22	20	18	16	14
AMP.	3	4	7	10	15

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL:

878104, 878107, 878109 : P.P. 878008, 878108 : NYLON

TERMINAL MATERIAL: BRASS

A.W.G.	ITEM NO.	W mm(inch)	L mm(inch)	COLOR	FIGURE
16-14	878104	20.0 (.787)	49.0 (1.929)	RED BLUE	 
18-14	878107	17.5 (.689)	31.0 (1.220)	BLUE BLACK	 
18-14	878109	28.0 (1.102)	31.0 (1.220)	BLACK	 
22-18	878008	35.0 (1.378)	34.0 (1.339)	RED	 
18-14	878108	35.0 (1.378)	34.0 (1.339)	BLUE	 