MC78L00A Series

Three-Terminal Low Current Positive Voltage Regulators

The MC78L00A Series of positive voltage regulators are inexpensive, easy–to–use devices suitable for a multitude of applications that require a regulated supply of up to 100 mA. Like their higher powered MC7800 and MC78M00 Series cousins, these regulators feature internal current limiting and thermal shutdown making them remarkably rugged. No external components are required with the MC78L00 devices in many applications.

These devices offer a substantial performance advantage over the traditional zener diode–resistor combination, as output impedance and quiescent current are substantially reduced.

- Wide Range of Available, Fixed Output Voltages
- Low Cost
- Internal Short Circuit Current Limiting
- Internal Thermal Overload Protection
- No External Components Required
- Complementary Negative Regulators Offered (MC79L00A Series)

Representative Schematic Diagram



Standard Application



A common ground is required between the input and the output voltages. The input voltage must remain typically 2.0 V above the output voltage even during the low point on the input ripple voltage.

*C_{in} is required if regulator is located an appreciable distance from power supply filter.

**C_O is not needed for stability; however, it does improve transient response.

ON Semiconductor
Formerly a Division of Motorola
http://onsemi.com



TO–92
P SUFFIX
CASE 29



SOP–8*
D SUFFIX
CASE 751

*SOP–8 is an internally modified SO–8 package. Pins 2, 3, 6, and 7 are electrically common to the die attach flag. This internal lead frame modification decreases package thermal resistance and increases power dissipation capability when appropriately mounted on a printed circuit board. SOP–8 conforms to all external dimensions of the standard SO–8 package.

PIN CONNECTIONS



(Top View)

DEVICE TYPE/NOMINAL VOLTAGE

5% Output Voltage Accuracy	Voltage
MC78L05AC	5.0
MC78L08AC	8.0
MC78L09AC	9.0
MC78L12AC	12
MC78L15AC	15
MC78L18AC	18
MC78L24AC	24

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 7 of this data sheet.

LOMEX KFT 1134 Budapest Lehel u.17 Tel.:349-5906 Fax.:320-3292 Honlap: www.lomex.hu E-mail: info@lomex.hu

© Semiconductor Components Industries, LLC, 1999

MAXIMUM RATINGS (T_A = +125°C, unless otherwise noted.)

Rating	Symbol	Value	Unit
Input Voltage (2.6 V–8.0 V) (12 V–18 V) (24 V)	V_I	30 35 40	Vdc
Storage Temperature Range	T_{stg}	–65 to +150	°C
Operating Junction Temperature Range	T_J	0 to +150	°C

ELECTRICAL CHARACTERISTICS (V_I = 10 V, I_O = 40 mA, C_I = 0.33 μF, C_O = 0.1 μF, –40°C < T_J < +125°C (for MC78LXXAB), 0°C < T_J < +125°C (for MC78LXXAC), unless otherwise noted.)

Characteristics	Symbol	MC78L05AC, AB			Unit
		Min	Typ	Max	
Output Voltage (T_J = +25°C)	V_O	4.8	5.0	5.2	Vdc
Line Regulation (T_J = +25°C, I_O = 40 mA) 7.0 Vdc ≤ V_I ≤ 20 Vdc 8.0 Vdc ≤ V_I ≤ 20 Vdc	Reg_{line}	 – –	 55 45	 150 100	mV
Load Regulation (T_J = +25°C, 1.0 mA ≤ I_O ≤ 100 mA) (T_J = +25°C, 1.0 mA ≤ I_O ≤ 40 mA)	Reg_{load}	 – –	 11 5.0	 60 30	mV
Output Voltage (7.0 Vdc ≤ V_I ≤ 20 Vdc, 1.0 mA ≤ I_O ≤ 40 mA) (V_I = 10 V, 1.0 mA ≤ I_O ≤ 70 mA)	V_O	 4.75 4.75	 – –	 5.25 5.25	Vdc
Input Bias Current (T_J = +25°C) (T_J = +125°C)	I_{IB}	 – –	 3.8 –	 6.0 5.5	mA
Input Bias Current Change (8.0 Vdc ≤ V_I ≤ 20 Vdc) (1.0 mA ≤ I_O ≤ 40 mA)	ΔI_{IB}	 – –	 – –	 1.5 0.1	mA
Output Noise Voltage (T_A = +25°C, 10 Hz ≤ f ≤ 100 kHz)	V_n	–	40	–	μV
Ripple Rejection (I_O = 40 mA, f = 120 Hz, 8.0 Vdc ≤ V_I ≤ 18 V, T_J = +25°C)	RR	41	49	–	dB
Dropout Voltage (T_J = +25°C)	$V_I – V_O$	–	1.7	–	Vdc

LOMEX KFT 1134 Budapest Lehel u.17 Tel.:349-5906 Fax.:320-3292 Honlap: www.lomex.hu E-mail: info@lomex.hu

ELECTRICAL CHARACTERISTICS (V_I = 14 V, I_O = 40 mA, C_I = 0.33 μF, C_O = 0.1 μF, –40°C < T_J < +125°C (for MC78LXXAB), 0°C < T_J < +125°C (for MC78LXXAC), unless otherwise noted.)

Characteristics	Symbol	MC78L08AC, AB			Unit
		Min	Typ	Max	
Output Voltage (T_J = +25°C)	V_O	7.7	8.0	8.3	Vdc
Line Regulation (T_J = +25°C, I_O = 40 mA) 10.5 Vdc ≤ V_I ≤ 23 Vdc 11 Vdc ≤ V_I ≤ 23 Vdc	Reg_{line}	 – –	 20 12	 175 125	mV
Load Regulation (T_J = +25°C, 1.0 mA ≤ I_O ≤ 100 mA) (T_J = +25°C, 1.0 mA ≤ I_O ≤ 40 mA)	Reg_{load}	 – –	 15 8.0	 80 40	mV
Output Voltage (10.5 Vdc ≤ V_I ≤ 23 Vdc, 1.0 mA ≤ I_O ≤ 40 mA) (V_I = 14 V, 1.0 mA ≤ I_O ≤ 70 mA)	V_O	 7.6 7.6	 – –	 8.4 8.4	Vdc
Input Bias Current (T_J = +25°C) (T_J = +125°C)	I_{IB}	 – –	 3.0 –	 6.0 5.5	mA
Input Bias Current Change (11 Vdc ≤ V_I ≤ 23 Vdc) (1.0 mA ≤ I_O ≤ 40 mA)	ΔI_{IB}	 – –	 – –	 1.5 0.1	mA
Output Noise Voltage (T_A = +25°C, 10 Hz ≤ f ≤ 100 kHz)	V_n	–	60	–	μV
Ripple Rejection (I_O = 40 mA, f = 120 Hz, 12 V ≤ V_I ≤ 23 V, T_J = +25°C)	RR	37	57	–	dB
Dropout Voltage (T_J = +25°C)	$V_I – V_O$	–	1.7	–	Vdc

ELECTRICAL CHARACTERISTICS (V_I = 15 V, I_O = 40 mA, C_I = 0.33 μF, C_O = 0.1 μF, –40°C < T_J < +125°C (for MC78LXXAB), 0°C < T_J < +125°C (for MC78LXXAC), unless otherwise noted.)

Characteristics	Symbol	MC78L09AC, AB			Unit
		Min	Typ	Max	
Output Voltage (T_J = +25°C)	V_O	8.6	9.0	9.4	Vdc
Line Regulation (T_J = +25°C, I_O = 40 mA) 11.5 Vdc ≤ V_I ≤ 24 Vdc 12 Vdc ≤ V_I ≤ 24 Vdc	Reg_{line}	 – –	 20 12	 175 125	mV
Load Regulation (T_J = +25°C, 1.0 mA ≤ I_O ≤ 100 mA) (T_J = +25°C, 1.0 mA ≤ I_O ≤ 40 mA)	Reg_{load}	 – –	 15 8.0	 90 40	mV
Output Voltage (11.5 Vdc ≤ V_I ≤ 24 Vdc, 1.0 mA ≤ I_O ≤ 40 mA) (V_I = 15 V, 1.0 mA ≤ I_O ≤ 70 mA)	V_O	 8.5 8.5	 – –	 9.5 9.5	Vdc
Input Bias Current (T_J = +25°C) (T_J = +125°C)	I_{IB}	 – –	 3.0 –	 6.0 5.5	mA
Input Bias Current Change (11 Vdc ≤ V_I ≤ 23 Vdc) (1.0 mA ≤ I_O ≤ 40 mA)	ΔI_{IB}	 – –	 – –	 1.5 0.1	mA
Output Noise Voltage (T_A = +25°C, 10 Hz ≤ f ≤ 100 kHz)	V_n	–	60	–	μV
Ripple Rejection (I_O = 40 mA, f = 120 Hz, 13 V ≤ V_I ≤ 24 V, T_J = +25°C)	RR	37	57	–	dB
Dropout Voltage (T_J = +25°C)	$V_I – V_O$	–	1.7	–	Vdc

LOMEX KFT 1134 Budapest Lehel u.17 Tel.:349-5906 Fax.:320-3292 Honlap: www.lomex.hu E-mail: info@lomex.hu

ELECTRICAL CHARACTERISTICS (V_I = 19 V, I_O = 40 mA, C_I = 0.33 μF, C_O = 0.1 μF, –40°C < T_J < +125°C (for MC78LXXAB), 0°C < T_J < +125°C (for MC78LXXAC), unless otherwise noted.)

Characteristics	Symbol	MC78L12AC, AB			Unit
		Min	Typ	Max	
Output Voltage (T_J = +25°C)	V_O	11.5	12	12.5	Vdc
Line Regulation (T_J = +25°C, I_O = 40 mA) 14.5 Vdc ≤ V_I ≤ 27 Vdc 16 Vdc ≤ V_I ≤ 27 Vdc	Reg_{line}	 – –	 120 100	 250 200	mV
Load Regulation (T_J = +25°C, 1.0 mA ≤ I_O ≤ 100 mA) (T_J = +25°C, 1.0 mA ≤ I_O ≤ 40 mA)	Reg_{load}	 – –	 20 10	 100 50	mV
Output Voltage (14.5 Vdc ≤ V_I ≤ 27 Vdc, 1.0 mA ≤ I_O ≤ 40 mA) (V_I = 19 V, 1.0 mA ≤ I_O ≤ 70 mA)	V_O	 11.4 11.4	 – –	 12.6 12.6	Vdc
Input Bias Current (T_J = +25°C) (T_J = +125°C)	I_{IB}	 – –	 4.2 –	 6.5 6.0	mA
Input Bias Current Change (16 Vdc ≤ V_I ≤ 27 Vdc) (1.0 mA ≤ I_O ≤ 40 mA)	ΔI_{IB}	 – –	 – –	 1.5 0.1	mA
Output Noise Voltage (T_A = +25°C, 10 Hz ≤ f ≤ 100 kHz)	V_n	–	80	–	μV
Ripple Rejection (I_O = 40 mA, f = 120 Hz, 15 V ≤ V_I ≤ 25 V, T_J = +25°C)	RR	37	42	–	dB
Dropout Voltage (T_J = +25°C)	$V_I – V_O$	–	1.7	–	Vdc

ELECTRICAL CHARACTERISTICS (V_I = 23 V, I_O = 40 mA, C_I = 0.33 μF, C_O = 0.1 μF, –40°C < T_J < +125°C (for MC78LXXAB), 0°C < T_J < +125°C (for MC78LXXAC), unless otherwise noted.)

Characteristics	Symbol	MC78L15AC, AB			Unit
		Min	Typ	Max	
Output Voltage (T_J = +25°C)	V_O	14.4	15	15.6	Vdc
Line Regulation (T_J = +25°C, I_O = 40 mA) 17.5 Vdc ≤ V_I ≤ 30 Vdc 20 Vdc ≤ V_I ≤ 30 Vdc	Reg_{line}	 – –	 130 110	 300 250	mV
Load Regulation (T_J = +25°C, 1.0 mA ≤ I_O ≤ 100 mA) (T_J = +25°C, 1.0 mA ≤ I_O ≤ 40 mA)	Reg_{load}	 – –	 25 12	 150 75	mV
Output Voltage (17.5 Vdc ≤ V_I ≤ 30 Vdc, 1.0 mA ≤ I_O ≤ 40 mA) (V_I = 23 V, 1.0 mA ≤ I_O ≤ 70 mA)	V_O	 14.25 14.25	 – –	 15.75 15.75	Vdc
Input Bias Current (T_J = +25°C) (T_J = +125°C)	I_{IB}	 – –	 4.4 –	 6.5 6.0	mA
Input Bias Current Change (20 Vdc ≤ V_I ≤ 30 Vdc) (1.0 mA ≤ I_O ≤ 40 mA)	ΔI_{IB}	 – –	 – –	 1.5 0.1	mA
Output Noise Voltage (T_A = +25°C, 10 Hz ≤ f ≤ 100 kHz)	V_n	–	90	–	μV
Ripple Rejection (I_O = 40 mA, f = 120 Hz, 18.5 V ≤ V_I ≤ 28.5 V, T_J = +25°C)	RR	34	39	–	dB
Dropout Voltage (T_J = +25°C)	$V_I – V_O$	–	1.7	–	Vdc

LOMEX KFT 1134 Budapest Lehel u.17 Tel.:349-5906 Fax.:320-3292 Honlap: www.lomex.hu E-mail: info@lomex.hu

ELECTRICAL CHARACTERISTICS (V_I = 27 V, I_O = 40 mA, C_I = 0.33 μF, C_O = 0.1 μF, 0°C < T_J < +125°C, unless otherwise noted.)

Characteristics	Symbol	MC78L18AC Min	MC78L18AC Typ	MC78L18AC Max	Unit
Output Voltage (T_J = +25°C)	V_O	17.3	18	18.7	Vdc
Line Regulation (T_J = +25°C, I_O = 40 mA) 21.4 Vdc ≤ V_I ≤ 33 Vdc 20.7 Vdc ≤ V_I ≤ 33 Vdc 22 Vdc ≤ V_I ≤ 33 Vdc 21 Vdc ≤ V_I ≤ 33 Vdc	Reg_{line}	 – –	 45 35	 325 275	mV
Load Regulation (T_J = +25°C, 1.0 mA ≤ I_O ≤ 100 mA) (T_J = +25°C, 1.0 mA ≤ I_O ≤ 40 mA)	Reg_{load}	 – –	 30 15	 170 85	mV
Output Voltage (21.4 Vdc ≤ V_I ≤ 33 Vdc, 1.0 mA ≤ I_O ≤ 40 mA) (20.7 Vdc ≤ V_I ≤ 33 Vdc, 1.0 mA ≤ I_O ≤ 40 mA) (V_I = 27 V, 1.0 mA ≤ I_O ≤ 70 mA) (V_I = 27 V, 1.0 mA ≤ I_O ≤ 70 mA)	V_O	 17.1 17.1	 – –	 18.9 18.9	Vdc
Input Bias Current (T_J = +25°C) (T_J = +125°C)	I_{IB}	 – –	 3.1 –	 6.5 6.0	mA
Input Bias Current Change (22 Vdc ≤ V_I ≤ 33 Vdc) (21 Vdc ≤ V_I ≤ 33 Vdc) (1.0 mA ≤ I_O ≤ 40 mA)	ΔI_{IB}	 – –	 – –	 1.5 0.1	mA
Output Noise Voltage (T_A = +25°C, 10 Hz ≤ f ≤ 100 kHz)	V_n	–	150	–	μV
Ripple Rejection (I_O = 40 mA, f = 120 Hz, 23 V ≤ V_I ≤ 33 V, T_J = +25°C)	RR	33	48	–	dB
Dropout Voltage (T_J = +25°C)	$V_I - V_O$	–	1.7	–	Vdc

ELECTRICAL CHARACTERISTICS (V_I = 33 V, I_O = 40 mA, C_I = 0.33 μF, C_O = 0.1 μF, 0°C < T_J < +125°C, unless otherwise noted.)

Characteristics	Symbol	MC78L24AC Min	MC78L24AC Typ	MC78L24AC Max	Unit
Output Voltage (T_J = +25°C)	V_O	23	24	25	Vdc
Line Regulation (T_J = +25°C, I_O = 40 mA) 27.5 Vdc ≤ V_I ≤ 38 Vdc 28 Vdc ≤ V_I ≤ 80 Vdc 27 Vdc ≤ V_I ≤ 38 Vdc	Reg_{line}	 – – –	 – 50 60	 – 300 350	mV
Load Regulation (T_J = +25°C, 1.0 mA ≤ I_O ≤ 100 mA) (T_J = +25°C, 1.0 mA ≤ I_O ≤ 40 mA)	Reg_{load}	 – –	 40 20	 200 100	mV
Output Voltage (28 Vdc ≤ V_I ≤ 38 Vdc, 1.0 mA ≤ I_O ≤ 40 mA) (27 Vdc ≤ V_I ≤ 38 Vdc, 1.0 mA ≤ I_O ≤ 40 mA) (28 Vdc ≤ V_I = 33 Vdc, 1.0 mA ≤ I_O ≤ 70 mA) (27 Vdc ≤ V_I ≤ 33 Vdc, 1.0 mA ≤ I_O ≤ 70 mA)	V_O	 22.8 22.8	 – –	 25.2 25.2	Vdc
Input Bias Current (T_J = +25°C) (T_J = +125°C)	I_{IB}	 – –	 3.1 –	 6.5 6.0	mA
Input Bias Current Change (28 Vdc ≤ V_I ≤ 38 Vdc) (1.0 mA ≤ I_O ≤ 40 mA)	ΔI_{IB}	 – –	 – –	 1.5 0.1	mA
Output Noise Voltage (T_A = +25°C, 10 Hz ≤ f ≤ 100 kHz)	V_n	–	200	–	μV
Ripple Rejection (I_O = 40 mA, f = 120 Hz, 29 V ≤ V_I ≤ 35 V, T_J = +25°C)	RR	31	45	–	dB
Dropout Voltage (T_J = +25°C)	$V_I - V_O$	–	1.7	–	Vdc

LOMEX KFT 1134 Budapest Lehel u.17 Tel.:349-5906 Fax.:320-3292 Honlap: www.lomex.hu E-mail: info@lomex.hu

Figure 1. Dropout Characteristics



Figure 2. Dropout Voltage versus Junction Temperature



Figure 3. Input Bias Current versus Ambient Temperature



Figure 4. Input Bias Current versus Input Voltage



Figure 5. Maximum Average Power Dissipation versus Ambient Temperature – TO–92 Type Package



Figure 6. SOP–8 Thermal Resistance and Maximum Power Dissipation versus P.C.B. Copper Length



LOMEX KFT 1134 Budapest Lehel u.17 Tel.:349-5906 Fax.:320-3292 Honlap: www.lomex.hu E-mail: info@lomex.hu

APPLICATIONS INFORMATION

Design Considerations

The MC78L00A Series of fixed voltage regulators are designed with Thermal Overload Protection that shuts down the circuit when subjected to an excessive power overload condition. Internal Short Circuit Protection limits the maximum current the circuit will pass.

In many low current applications, compensation capacitors are not required. However, it is recommended that the regulator input be bypassed with a capacitor if the regulator is connected to the power supply filter with long wire lengths, or if the output load capacitance is large. The input bypass capacitor should be selected to provide good high–frequency characteristics to insure stable operation under all load conditions. A 0.33 μF or larger tantalum, mylar, or other capacitor having low internal impedance at high frequencies should be chosen.The bypass capacitor should be mounted with the shortest possible leads directly across the regulators input terminals. Good construction techniques should be used to minimize ground loops and lead resistance drops since the regulator has no external sense lead. Bypassing the output is also recommended.

Figure 7. Current Regulator



The MC78L00 regulators can also be used as a current source when connected as above. In order to minimize dissipation the MC78L05C is chosen in this application. Resistor R determines the current as follows:

$$I_O = \frac{5.0\ V}{R} + I_B$$

I_{IB} = 3.8 mA over line and load changes

For example, a 100 mA current source would require R to be a 50 Ω, 1/2 W resistor and the output voltage compliance would be the input voltage less 7 V.

Figure 8. ± 15 V Tracking Voltage Regulator



Figure 9. Positive and Negative Regulator



ORDERING INFORMATION

Device	Operating Temperature Range	Package	Shipping
MC78LXXACD*	T_J = 0° to +125°C	SOP–8	98 Units / Rail
MC78LXXACDR2*		SOP–8 / Tape & Reel	2500 Units / Tape & Reel
MC78LXXACP		TO–92	2000 Units / Bag
MC78LXXACPRA / MC78LXXACPRE		TO–92 / Tape & Reel	2000 Units / Tape & Reel
MC78LXXACPRM / MC78LXXACPRP		TO–92 / Ammo Pack	2000 Units / Ammo Pack
MC78LXXABD*	T_J = –40° to +125°C	SOP–8	98 Units / Rail
MC78LXXABDR2*		SOP–8 / Tape & Reel	2500 Units / Tape & Reel
MC78LXXABP*		TO–92	2000 Units / Bag
MC78LXXABPRA / MC78LXXABPRE		TO–92 / Tape & Reel	2000 Units / Tape & Reel
MC78LXXABPRM / MC78LXXABPRP		TO–92 / Ammo Pack	2000 Units / Ammo Pack

XX indicates nominal voltage
*Available in 5, 8, 9, 12 and 15 V devices.

LOMEX KFT 1134 Budapest Lehel u.17 Tel.:349-5906 Fax.:320-3292 Honlap: www.lomex.hu E-mail: info@lomex.hu

PACKAGE DIMENSIONS

P SUFFIX
PLASTIC PACKAGE
CASE 29–04
ISSUE AD



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. DIMENSION F APPLIES BETWEEN P AND L. DIMENSION D AND J APPLY BETWEEN L AND K MINIMUM. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.022	0.41	0.55
F	0.016	0.019	0.41	0.48
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	—	12.70	—
L	0.250	—	6.35	—
N	0.080	0.105	2.04	2.66
P	—	0.100	—	2.54
R	0.115	—	2.93	—
V	0.135	—	3.43	—

(SOP–8)
D SUFFIX
PLASTIC PACKAGE
CASE 751–05
ISSUE R



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. DIMENSIONS ARE IN MILLIMETERS.
3. DIMENSION D AND E DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 PER SIDE.
5. DIMENSION B DOES NOT INCLUDE MOLD PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 TOTAL IN EXCESS OF THE B DIMENSION AT MAXIMUM MATERIAL CONDITION.

	MILLIMETERS	
DIM	MIN	MAX
A	1.35	1.75
A1	0.10	0.25
B	0.35	0.49
C	0.18	0.25
D	4.80	5.00
E	3.80	4.00
e	1.27 BSC	
H	5.80	6.20
h	0.25	0.50
L	0.40	1.25
θ	0°	7°

LOMEX KFT 1134 Budapest Lehel u.17 Tel.:349-5906 Fax.:320-3292 Honlap: www.lomex.hu E-mail: info@lomex.hu

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

USA/EUROPE Literature Fulfillment:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303–675–2175 or 800–344–3860 Toll Free USA/Canada
Fax: 303–675–2176 or 800–344–3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com

Fax Response Line*: 303–675–2167
800–344–3810 Toll Free USA/Canada
*To receive a Fax of our publications

N. America Technical Support: 800–282–9855 Toll Free USA/Canada

ASIA/PACIFIC: LDC for ON Semiconductor – Asia Support
Phone: 303–675–2121 (Tue–Fri 9:00am to 1:00pm, Hong Kong Time)
Email: ONlit–asia@hibbertco.com

JAPAN: ON Semiconductor, Japan Customer Focus Center
4–32–1 Nishi–Gotanda, Shinagawa–ku, Tokyo, Japan 141–8549
Phone: 81–3–5487–8345
Email: r14153@onsemi.com

ON Semiconductor Website: http://onsemi.com

For additional information, please contact your local Sales Representative.