


## Schottky Rectifier



### Features

- Ideal for automated placement
- Low power losses
- High forward surge capability

### Typical Applications

For use in lighting, fast switching rectification of power suppliers, inverters, converters, and freewheeling diodes for consumer, automotive, and telecommunication.

### Mechanical Data

- **Package:** TO-277  
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, Halogen free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

### ■Maximum Ratings (T<sub>a</sub>=25°C Unless otherwise specified)

| PARAMETER                                                                                      | SYMBOL           | UNIT             | SS15U60   |
|------------------------------------------------------------------------------------------------|------------------|------------------|-----------|
| Device marking code                                                                            |                  |                  | SS15U60   |
| Repetitive Peak Reverse Voltage                                                                | V <sub>RRM</sub> | V                | 60        |
| Average Rectified Output Current<br>@60Hz -sine wave, R- load, T <sub>a</sub> =85°C            | I <sub>O</sub>   | A                | 15        |
| Forward Surge Current (Non-repetitive)<br>@ 60Hz Half-sine wave, 1 cycle, T <sub>a</sub> =25°C | I <sub>FSM</sub> | A                | 275       |
| Current Squared Time @1ms≤t≤8.3ms T <sub>j</sub> =25°C                                         | I <sup>2</sup> t | A <sup>2</sup> s | 313       |
| Storage Temperature                                                                            | T <sub>stg</sub> | °C               | -55 ~+150 |
| Junction Temperature                                                                           | T <sub>j</sub>   | °C               | -55 ~+150 |

### ■Electrical Characteristics (T<sub>a</sub>=25°C Unless otherwise specified)

| PARAMETER                 | SYMBOL          | UNIT | TEST CONDITIONS                               | Min | Typ  | Max  |
|---------------------------|-----------------|------|-----------------------------------------------|-----|------|------|
| Peak Forward Voltage      | V <sub>FM</sub> | V    | I <sub>FM</sub> =15.0A, T <sub>j</sub> =25°C  | -   | 0.52 | 0.55 |
|                           |                 |      | I <sub>FM</sub> =15.0A, T <sub>j</sub> =125°C | -   | 0.53 | 0.60 |
| Reverse Breakdown Voltage | V <sub>BR</sub> | V    | I <sub>R</sub> =0.5mA                         | 60  | -    | -    |
| Leakage Current           | I <sub>R</sub>  | mA   | V <sub>R</sub> =60V, T <sub>j</sub> =25°C     | -   | -    | 0.5  |
|                           |                 |      | V <sub>R</sub> =60V, T <sub>j</sub> =125°C    | -   | -    | 50   |



# SS15U60

## ■ Thermal Characteristics ( $T_a=25^{\circ}\text{C}$ Unless otherwise specified)

| PARAMETER          |                  | SYMBOL                 | UNIT                 | SS15U60 |
|--------------------|------------------|------------------------|----------------------|---------|
| Thermal Resistance | Junction to Case | $R_{\theta\text{J-C}}$ | $^{\circ}\text{C/W}$ | 8       |

## ■ Ordering Information (Example)

| PREFERRED P/N | PACKAGE CODE | UNIT WEIGHT(g)     | MINIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|---------------|--------------|--------------------|----------------------|-------------------------|----------------------------|---------------|
| SS15U60       | F1           | Approximate 0.0828 | 5000                 | 10000                   | 80000                      | 13" reel      |

## ■ Characteristics(Typical)

FIG.1:  $I_o$ - $T_c$  Curve




FIG.2: Forward Surge Current Capability




FIG.3: Forward Voltage






FIG.4: Typical Reverse Characteristics






## SS15U60

### ■ Outline Dimensions



| TO-277 |         |         |
|--------|---------|---------|
| Dim    | Min(mm) | Max(mm) |
| A      | 3.9     | 4.1     |
| B      | 1.7     | 1.9     |
| C      | 6.4     | 6.6     |
| D      | 5.3     | 5.5     |
| E      | 0.8     | 1.0     |
| F      | 1.8     | 1.9     |
| G      | 0.35    | 0.45    |
| H      | 1.10    | 1.20    |
| I      | 4.1     | 4.5     |
| J      | 1.5     | 1.9     |

### ■ Suggested pad layout



| Dim | Min(mm) |
|-----|---------|
| A   | 3.36    |
| B   | 4.86    |
| C   | 0.85    |
| P   | 1.84    |
| Q1  | 1.4     |
| Q2  | 1.4     |



### Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.