


VINYL-INSULATED (EASY ENTRY) SPADE TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14
AMP.	9	12	17	18	30

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.
INSULATION MATERIAL: VINYL
INSULATION COLOR:

 22-16 A.W.G.: RED ■ 16-14 A.W.G.: BLUE ■
TERMINAL MATERIAL: COPPER


WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE		DIMENSION ^{inch} mm							CRIMPING TOOL	Q'TY BOX		
	BRAZED SEAM	BUTTED SEAM	d2		W	F	L	E	D	d1	T				
22-16 A.W.G. 0.5-1.5 mm ²	SVEB1-3.2	SVE1-3.2	#4	.126 3.2	.224 5.7	.256 6.5	.874 22.2	.441 11.2	.157 4.0	.067 1.7	.030 0.75	IZUMI MODEL 34 WITH DIE INDEX COLOR:RED OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:RED	1000		
	SVEBS1-3.7	SVES1-3.7	#6	.146 3.7									1000		
	SVEBL1-3.7	SVEL1-3.7	#6	.146 3.7									.252 6.4	1000	
	SVEBLL1-3.7	SVELL1-3.7	#6	.146 3.7									.283 7.2	1000	
	SVEBS1-4	SVES1-4	#8	.169 4.3	.252 6.4								1000		
	SVEBM1-4	SVEM1-4	#8	.169 4.3	.283 7.2								1000		
	SVEBL1-4	SVEL1-4	#8	.169 4.3	.319 8.1								1000		
	SVEBS1-5	SVES1-5	#10	.209 5.3									1000		
	SVEBL1-5	SVEL1-5	#10	.209 5.3									.374 9.5	1000	
	SVEBS1-6	SVES1-6	1/4	.252 6.4									1000		
	SVEBL1-6	SVEL1-6	1/4	.252 6.4	.472 12.0								.433 11.0	1.110 28.2	1000
	SVEB1-8	SVE1-8	5/16	.331 8.4	.551 14.0								.394 10.0	1.083 27.5	1000
16-14 A.W.G. 1.5-2.5 mm ²	SVEB2-3.2	SVE2-3.2	#4	.126 3.2	.224 5.7	.256 6.5	.886 22.5	.453 11.5	.177 4.5	.091 2.3	.031 0.8	IZUMI MODEL 34 WITH DIE INDEX COLOR:BLUE OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:BLUE	1000		
	SVEBS2-3.7	SVES2-3.7	#6	.146 3.7									1000		
	SVEBL2-3.7	SVEL2-3.7	#6	.146 3.7									.236 6.0	1000	
	SVEBLL2-3.7	SVELL2-3.7	#6	.146 3.7									.283 7.2	1000	
	SVEBS2-4	SVES2-4	#8	.169 4.3	.252 6.4								1000		
	SVEBM2-4	SVEM2-4	#8	.169 4.3	.283 7.2								1000		
	SVEBL2-4	SVEL2-4	#8	.169 4.3	.311 7.9								1000		
	SVEBS2-5	SVES2-5	#10	.209 5.3									1000		
	SVEBL2-5	SVEL2-5	#10	.209 5.3									.366 9.3	1000	
	SVEBS2-6	SVES2-6	1/4	.252 6.4									1000		
	SVEBL2-6	SVEL2-6	1/4	.252 6.4	.472 12.0								.433 11.0	1.110 28.5	1000
	SVEB2-8	SVE2-8	5/16	.331 8.4	.551 14.0								.344 10.0	1.094 27.8	1000
	SVEB2-10	SVE2-10	3/8	.413 10.5	.689 17.5								.512 13.0	1.268 32.2	1000