


VINYL-INSULATED SPADE TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	14	12	10	8
AMP.	30	35	50	70

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.
INSULATION MATERIAL: VINYL
INSULATION COLOR:

14-12 A.W.G.: BLACK 12-10 A.W.G.: YELLOW 8 A.W.G.: RED

TERMINAL MATERIAL: COPPER


WIRE RANGE A.W.G. mm²	ITEM NO.		STUD SIZE		DIMENSION inch mm							CRIMPING TOOL	Q'TY BOX
	BRAZED SEAM	BUTTED SEAM	d2		W	F	L	E	D	d1	T		
14-12 A.W.G. 2.5-4 mm²	SVB3-3.7	SV3-3.7	#6	.146 3.7	.315 8.0							IZUMI MODEL 214 WITH DIE INDEX COLOR:BLACK OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:BLACK	1000
	SVBS3-4	SVS3-4	#8	.146 3.7	.283 7.2								1000
	SVB3-4	SV3-4	#8	.169 4.3									1000
	SVB3-5	SV3-5	#10	.209 5.3									1000
	SVB3-6	SV3-6	1/4	.252 6.4	.472 12.0	.358 9.1	1.122 28.5						1000
12-10 A.W.G. 4-6 mm²	SVBS5-3.7	SVS5-3.7	#6	.146 3.7	.283 7.2	.295 7.5	.961 24.4					IZUMI MODEL 5 WITH DIE INDEX COLOR:YELLOW OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:YELLOW	500
	SVB5-3.7	SV5-3.7 *	#6	.146 3.7	.327 8.3	.276 7.0	1.004 25.5						500
	SVBSS5-4	SVSS5-4	#8	.169 4.3	.283 7.2	.295 7.5	.961 24.4						500
	SVBS5-4	SVS5-4 *	#8	.169 4.3	.327 8.3								500
	SVBL5-4	SVL5-4 *	#8	.169 4.3									500
	SVB5-5	SV5-5 *	#10	.209 5.3	.354 9.0	.276 7.0	1.004 25.5	.512 13.0	.252 6.4	.134 3.4	.039 1.0		500
	SVBS5-6	SVS5-6 *	1/4	.252 6.4									500
	SVBL5-6	SVL5-6 *	1/4	.252 6.4	.472 12.0	.472 12.0	1.240 31.5						500
	SVB5-8	SV5-8	5/16	.331 8.4	.551 14.0	.413 10.5	1.201 30.5						500
8 A.W.G. 8 mm²	SVB8-4	SV8-4	#8	.169 4.3	.413 10.5	.319 8.1	1.142 29.0	.657 16.7	.335 8.5	.177 4.5	.047 1.2		500



ALL LISTED

*: ADDITIONAL



CERTIFIED