

■ 图示(Pic. shown) : TLPS-100V-08P-G12S

General.	PCB Connector	Rated : 150V,10A , 1.5mm ²
	Single row , 3.81mm pitch , 02-24 Pole	
	Wiring orientation: 180°(wire to plug-in)	
	Screw clamp unit: M2.0, 0.2Nm Max	

认证 (Approval) :



技术参数Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	--	150V	--
额定电流(Rated current)	8A	--	8A	--	10A	--
额定连接容量(Rated connection capacity)	24-14AWG Sol&Str			0.34-1.5mm ²		
绝缘材料(Insulation Material)	PA66 UL94 V-0					
电流承载部件材料和镀层(Material & Plating of Current carrier)	Copper alloy , Tin plated					
接线弹片材料(Material of Clamp spring)	--					
绝缘电阻(Insulation Resistance)	500MΩ or more at DC500V					
耐电压(1分钟)(Withstanding Voltage/1Min)	2000V					
额定冲击电压(Rated surge voltage)	--					
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)	M2.0 , 0.2Nm Max					
固定螺丝(Mounting Screw) , 扭矩(torque)	--					
剥线长度(Wire stripping length)	6.0mm					
使用温度(Operating temperature)	-40°C up to +105°C					
焊接方式(Soldering recommend)	--					

■ 订购方式(How to order)

TLPS	1	00	V	XXXX	XXP	G12	S
Series No. 系列号	Pitch间距 1=3.81mm	Differentiate Number 区分号	Connection angle 角度 V=180° wire to plug-in	Special code 特编号 XXXX=custom-made blank=standard	No. of Poles 极数 02-24P	Color 颜色 Green: G12	Screw Type 螺丝S=Slot C=Cross

针座 (Pin header) — single row



P/N : TLPHC-100V
Orientation :
90° (plug-in to board)
Rated:150V,10A
Closed side



P/N : TLPHC-100R
Orientation :
180° (plug-in to board)
Rated:150V,10A
Closed side




P/N : TLPHC-104
Orientation :
135° (plug-in to board)
Rated:250V,10A
Closed side

针座 (Pin header) — dual row in 1 plane



P/N : TLPHDC-108V
Orientation :
90° (plug-in to board)
Rated:160V,8A
Closed side



P/N : TLPHDC-108R
Orientation :
180° (plug-in to board)
Rated:160V,8A
Closed side

针座 (Pin header) — dual row staggered



P/N : TLPHDC-105V
Orientation :
90° (plug-in to board)
Rated:160V,8A
Closed side



P/N : TLPHDC-105R
Orientation :
180° (plug-in to board)
Rated:160V,8A
Closed side