


PCB Connector — TLP series (Female Connector)— TLPS-500V



■ 图示(Pic. shown) : TLPS-500V-04P-G12S

General.	PCB Connector	Rated : 630V,20A , 2.5mm ²
	Single row , 7.62mm pitch , 02-24 Pole	
	Wiring orientation: 180°(wire to plug-in)	
	Screw clamp unit: M3.0, 0.5Nm Max	

认证 (Approval) :   

■ 技术参数Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	--	630V	--
额定电流(Rated current)	16A	--	10A	--	20A	--
额定连接容量(Rated connection capacity)	30-12AWG Sol&Str			0.2~2.5mm ² Sol&Str,4.0mm ² Sol Max		
绝缘材料(Insulation Material)				PA66 UL94 V-0		
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Tin plated		
接线弹片材料(Material of Clamp spring)				--		
绝缘电阻(Insulation Resistance)				500MΩ or more at DC500V		
耐电压(1分钟)(Withstanding Voltage/1Min)				2500V		
额定冲击电压(Rated surge voltage)				--		
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				M3.0 , 0.5Nm Max		
固定螺丝(Mounting Screw) , 扭矩(torque)				--		
剥线长度(Wire stripping length)				7.0mm		
使用温度(Operating temperature)				-40°C up to +105°C		
焊接方式(Soldering recommend)				--		

■ 订购方式(How to order)

TLPS	5	00	V	XXXX	XXP	G12	S
Series No. 系列号	Pitch间距 5=7.62mm	Differentiate Number 区分号	Connection angle 角度 V=180° wire to plug-in	Special code 特编号 XXXX=custom-made blank=standard	No. of Poles 极数 02-24P	Color 颜色 Green: G12	Screw Type 螺丝S=Slot C=Cross

■ 针座 (Pin header) — single row



P/N : TLPH-500V
Orientation :
90° (plug-in to board)
Rated:630V,20A
Open side



P/N : TLPHC-500V
Orientation :
90° (plug-in to board)
Rated:630V,20A
Closed side



P/N : TLPH-500R
Orientation :
180° (plug-in to board)
Rated:630V,20A
Open side



P/N : TLPHC-500R
Orientation :
180° (plug-in to board)
Rated:630V,20A
Closed side