




TS1085

3A Low Dropout Positive Voltage Regulator



Low Dropout Voltage 1.5V max.

General Description


The TS1085 Series are high performance positive voltage regulators are designed for use in applications requiring low dropout performance at full rated current. Additionally, the TS1085 Series provides excellent regulation over variations due to changes in line, load and temperature. Outstanding features include low dropout performance at rated current, fast transient response, internal current limiting and thermal shutdown protection of the output device. The TS1085 Series are three terminal regulators with fixed and adjustable voltage options available in popular packages.

This series is offered in 3-pin TO-263, TO-220 and TO-252 package.

Features

- ✧ Low dropout performance 1.5V max.
- ✧ Full current rating over line and temperature.
- ✧ Fast transient response
- ✧ $\pm 2\%$ Total output regulation over line, load and temperature
- ✧ Adjust pin current max $90 \mu A$ over temperature
- ✧ Line regulation typical 0.015%.
- ✧ Load regulation typical 0.05%.
- ✧ Fixed/adjustable output voltage
- ✧ TO-220, TO-263 and TO-252 package

Block Diagram



Ordering Information

Part No.	Operating Temp.	Package
TS1085CZxx	0 ~ +125 °C	TO-220
TS1085CMxx		TO-263
TS1085CPxx		TO-252

Note: Where xx denotes voltage option, available are 5.0V, 3.3V, 2.5V and 1.5V Leave blank for adjustable version. Contact factory for additional voltage options.

Absolute Maximum Rating

Input Supply Voltage	V _{in}	12	V
Operation Input Supply Voltage	V _{in} (operate)	7	V
Power Dissipation	P _D	Internally Limited	W
Operating Junction Temperature Range	T _J	0 ~ +125	°C
Storage Temperature Range	T _{STG}	-65 ~ +150	°C
Lead Soldering Temperature (260 °C)			
TO-220 / TO-263 Package		10	S
TO-252 Package		5	



Electrical Characteristics					
Ta = 25 °C, unless otherwise specified. Adjustable version test with Vout = 2.5V.					
Parameter	Conditions	Min	Typ	Max	Unit
Output Voltage	$V_{out}+1.5V \leq V_{in} \leq 7V$, $I_o=3A$	$0.980 V_o $	5.0 / 3.3 2.5 / 1.5	$1.020 V_o $	V
Reference Voltage	$(V_{in-out}) = 1.5V$, $I_o=3A$	$0.980 V_o $	1.25	$1.020 V_o $	V
Input Supply Voltage		--	--	7	V
Line Regulation	$V_{out}+1.5V \leq V_{in} \leq 7V$, $I_o=10mA$	--	0.015	0.2	%
Load Regulation (note 1,2)	$V_{in}=V_{out}+1.5V$, $10mA \leq I_o \leq 3A$	--	0.05	1.0	%
Dropout Voltage	$I_o=3A$, $\Delta V_{out}=0.1\%V_{out}$	--	1.3	1.5	V
Minimum Load Current	$V_{in}=5V$	--	8	10	mA
Adjustable Pin Current		--	90	--	uA
Current Limit	$V_{in} - V_{out}=3V$	3.5	--	--	A
Temperature Stability	$I_o=10mA$	--	0.5	--	%
Ripple Rejection	$F = 120Hz$, $I_o=3A$ $C_{out}=25\mu F$, $V_{in}=V_{out} + 3V$	--	60	70	dB


Thermal Performance			
Condition	Package type	Typ	Unit
Thermal Resistance Junction to Ambient	TO-220	80	°C/W
	TO-263	85	
	TO-252	105	

Note 1: See thermal regulation specification for changes in output voltage due to heating effects. Line and load regulation are measured at a constant junction temperature by low duty cycle pulse testing. Load regulation is measured at the output lead = 1/18" from the package.


Note 2: Line and load regulation are guaranteed up to the maximum power dissipation of 15W. Power dissipation is determined by the input / output voltage difference and the output current. Guaranteed maximum power dissipation will not be available over the full input / output voltage range.

Note 3: Quiescent current is defined as the minimum output current required to maintain the regulation.

Typical Application Circuit



Fixed output voltage version



$$V_{out} = V_{ref} * (1 + R2 / R1)$$

* C_{in} is requested if regulator is located
Far from power supply filter

** Design C_{out} as close to V_{out} pin as
possible

Adjustable output voltage version

Electrical Characteristics Curve

Figure 1: dropout voltage v.s. output current




Figure 2: load regulation v.s. temp.




Figure 3: output change v.s. temp.




Figure 4: line regulation




Figure 5: line transient response






Figure 6: load transient response




TO-220 Mechanical Drawing




TO-220 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	10.000	10.500	0.394	0.413
B	3.240	4.440	0.128	0.175
C	2.440	2.940	0.096	0.116
D	-	6.350	-	0.250
E	0.381	1.106	0.015	0.040
F	2.345	2.715	0.092	0.058
G	4.690	5.430	0.092	0.107
H	12.700	14.732	0.500	0.581
I	8.382	9.017	0.330	0.355
J	14.224	16.510	0.560	0.650
K	3.556	4.826	0.140	0.190
L	0.508	1.397	0.020	0.055
M	27.700	29.620	1.060	1.230
N	2.032	2.921	0.080	0.115
O	0.255	0.610	0.010	0.024
P	5.842	6.858	0.230	0.270

TO-263 Mechanical Drawing



TO-263 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	10.000	10.500	0.394	0.413
B	14.605	15.875	0.575	0.625
C	0.508	0.991	0.020	0.039
D	2.420	2.660	0.095	0.105
E	4.064	4.830	0.160	0.190
F	1.118	1.400	0.045	0.055
G	0.450	0.730	0.018	0.029
H	8.280	8.800	0.325	0.346
I	1.140	1.400	0.044	0.055
J	1.480	1.520	0.058	0.060

TO-252 Mechanical Drawing



TO-252 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	6.570	6.840	0.259	0.269
B	9.250	10.400	0.364	0.409
C	0.550	0.700	0.022	0.028
D	2.560	2.670	0.101	0.105
E	2.300	2.390	0.090	0.094
F	0.490	0.570	0.019	0.022
G	1.460	1.580	0.057	0.062
H	0.520	0.570	0.020	0.022
I	5.340	5.550	0.210	0.219
J	1.460	1.640	0.057	0.065