







The information provided herein is from CONNLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNLY or its affiliates. Unauthorized use or reproduction of this document in any form or by any means, electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without the prior written permission of CONNLY is strictly prohibited. CONNLY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.




(Series Image-Reference Only)




Recommend PCB Layout(Tolerance:±0.05)



V/T type



R/A type



Elevator type

Dimension

Position	A	B	C				
06	15.22	13.02	5.08				
08	17.76	15.56	7.62				
10	20.30	18.10	10.16				
12	22.84	20.64	12.70	30	45.70	43.50	35.56
14	25.38	23.18	15.24	34	50.78	48.58	40.64
16	27.92	25.72	17.78	40	58.40	56.20	48.26
20	33.00	30.80	22.86	50	71.10	68.90	60.96
24	38.08	35.88	27.94	60	83.80	81.60	73.66
26	40.62	38.42	30.48	64	88.88	86.68	78.74

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LJH 09/20/05'		LJC 09/20/05'
B	ADD P/N CODE	YCH 12/02/13'		LJC 12/02/13'
C	DRAWING UPDATE	JLZ 11/09/17'	HZW 11/09/17'	LJC 11/09/17'
G	DRAWING UPDATE	JLZ 08/24/18'		

NOTES:

1. Electrical characteristics:

- 1.1 Contact resistance: 20mΩ Max. Initial.
- 1.2 Dielectric withstanding voltage: 500V AC(rms) for 1 minute.
- 1.3 Insulation resistance: 1000MΩ Min.
- 1.4 Current rating:3A.

2. Environment characteristics:

Temperature range: -40°C~+105°C.

3. Product number code:

DS1013- X X X X X X - X

- Housing material
0: PBT UL94 V-0
9: PA-9T
- Plating level
3A: Level B N: Level N
- DIM. H type(For elevator only)
1: 7.50
2: 9.50
- DIM. E type(For V/T only)
1: 3.10
2: 8.00
- Housing color
B: Black U: Blue
W: White A: Gray
- Contact plating
Si: Full gold flash
- Mounting type
S: V/T type
R: R/A type
E: Elevator type
- No.of contacts
06 08 10 12 14 16 20 24
26 30 34 40 50 60 64

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE		CUSTOMER	
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C-DS1013-XXXX-X-X-G		

PROJECTION	TITLE	2.54mm BOX HEADER R/A, V/T & ELEVATOR TYPE	
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1013 SERIES
 晨翔电子有限公司 CONNFLY CONNLY ELECTRONIC CO. LTD			